



Wall-Mounted EV Charger

Innovative


- ▶ Type 2 cable / Type 2 socket
- ▶ Wall-mount / Floor-stand
- ▶ Start modes: RFID/Plug&Play /App
- ▶ From 0-500Km cost around 3.5 hours (22KW)

Secure and Safe

- ▶ 30mA Type A +6mA DC residual current protection
- ▶ IP65 waterproof / IK10 explosion-proof
- ▶ Multiple protection to ensure the users safety

Intelligent

- ▶ Multi communications(WiFi/4G/BLE)
- ▶ App charging scheduling
- ▶ OCPP communication protocol with CMS



Model	FF-EU332EA-SV	FF-EU332EA-SV
Standard	EU	EU
Power	7kW	11/22kW
Input Voltage	230VAC ±10%	400VAC ±10%
Output Voltage	230VAC	400VAC
Input Frequency	50/60Hz	50/60Hz
Output Current	32A	16A/32A adjustable
Rated Residual Operating Current	AC30mA+DC6mA	AC30mA+DC6mA
Over Temperature Protection	≥95℃	≥95℃
Mean Time Between Failure	MTBF≥30000h	MTBF≥30000h
Charging Start Mode	Plug and play,RFID,APP	Plug and play,RFID,APP
APP/Communication	Support/WiFi/BLE/4G Optional	Support/WiFi/BLE/4G Optional
Relative Humidity	5%-95% No condensation	5%-95% No condensation
Maximum Altitude	2000m	2000m
Life Time Of Connector	≥10000 times	≥10000 times
Operating /Storage Temperature	-30℃ ~ +50℃ /-40℃ ~ +85℃	-30℃ ~ +50℃ /-40℃ ~ +85℃
Cable Length	5 meters (Customizable)	5 meters (Customizable)
Wiring Method	Enter and out at the bottom	Enter and out at the bottom
Connector Type	IEC 62196-2 Type 2	IEC 62196-2 Type 2
Power Plug	EU (Standard)	EU (Standard)
Weight	1.8 Kg (cable not included)	1.8 Kg (cable not included)
Color	White/Black/Dark Grey	White/Black/Dark Grey
Host Dimension	311*192*80mm	311*192*80mm
Waterproof/ Explosionproof	Charging Connector IP54,Host IP66/IK10	Charging Connector IP54,Host IP66/IK10
Certification Standard	ENEC61851-1:2019,IEC61851-1:2017,IEC61851-21-2:2018	ENEC61851-1:2019,IEC61851-1:2017,IEC61851-21-2:2018



Wall-Mounted EV Charger