

FLYFINE



Portable Mode 2 EV Charger

Innovative

- ▶ Connector Type: SAE J1772 Type 1
- ▶ Charging Mode: Plug&Play

Secure and Safe

- ▶ CCID20 Rated Residual Operating Current
- ▶ Charging Connector IP54, Host IP66
- ▶ Multiple Protection To Ensure The Users Safety

Intelligent

- ▶ Indicator Lights
(Power/Charging/Error)



FLYFINE

Model	FF-AC240US1
Standard	US
Power	9.6kW
Input / Output Voltage	208 ~ 240VAC / 208 ~ 240VAC
Output Current	16A/32A/40A adjustable
Over Temperature Protection	>95°C
Rated Residual Operating Current	CCID20
Charging Mode	Plug and Play
Operating Temperature	-30°C ~ +50°C
Storage Temperature	-40°C ~ +85°C
Relative Humidity	5%-95% No condensation
Life Time Of Connector	≥10000 times
Mean Time Between Failure	MTBF≥30000h
Metal Wire Sectional Area	8.37mm²
Cable Length	5 meters (Customizable)
Weight	5 Kg (with cable)
Color	Black/White
Power Plug	NEMA 14-50
Connector Type	SAE J1772 Type 1
Maximum Altitude	2000m
Indicator Lights	Power/Charging/Error
Degree Of Protection	Charging Connector IP54, Host IP66
Host Dimension	255*96*63(mm)



Portable Mode 2 EV Charger