

FLYFINE



Wall-Mounted EV Charger

Innovative

- ▶ Type 2 cable / Type 2 socket
- ▶ Wall-mount / Floor-stand
- ▶ Start modes: RFID/Plug&Play / App

Secure and Safe

- ▶ CCID20 residual current protection
- ▶ Charging Connector IP54, Host IP66/IK10
- ▶ Multiple protection to ensure the users safety

Intelligent

- ▶ Multi communications(WiFi/4G/BLE)
- ▶ App charging scheduling



Residential Area



Parking Lot



Commercial Building



Fleet

FLYFINE

Model	FF-AC3111USH-LJK
Standard	US
Power	11.5kW
Input / Output Voltage	208 ~ 240VAC / 208 ~ 240VAC
Input Frequency	50/60Hz
Output Current	16A/24A/32A/40A/48A adjustable
Over Temperature Protection	≥95℃
Rated Residual Operating Current	CCID20
Charging Start Mode	Plug and Play, RFID, APP
Operating Temperature	-30℃ ~ +50℃
Storage Temperature	-40℃ ~ +85℃
Relative Humidity	5%-95% No condensation
Life Time Of Connector	≥10000 times
Mean Time Between Failure	MTBF≥30000h
APP/Communication	Support/WIFI BLE, 4G Optional
Cable Length	5 meters (Customizable)
Weight	1.8 Kg (cable not included)
Color	White/Black/Dark Grey
Power Plug	EU (Standard)
Connector Type	IEC 62196-2 Type 2
Maximum Altitude	2000m
Degree Of Protection	Charging Connector IP54, Host IP66/IK10
Host Dimension	296*192*77(mm)
Wiring Method	Enter and out at the bottom



Wall-Mounted EV Charger